

Technical drawing of a PCB assembly showing three views: top, side, and bottom.

Top View: The PCB is rectangular with overall dimensions of 88 mm (width) and 98 mm (height). The central area contains a 4x4 grid of 16 square pads, each with a side length of 14 mm. The pads are spaced 6.25 mm apart. The outer frame has a thickness of 4.5 mm and rounded corners with a radius of R1. The mounting holes are located at the corners, with a diameter of 4.9 mm and a radius of R2.5. The distance between the mounting holes is 68 mm.

Side View: The PCB has a thickness of 2.7 mm. The mounting holes are located at the corners, with a diameter of 4.9 mm and a radius of R2.5. The distance between the mounting holes is 68 mm.

Bottom View: The PCB has a thickness of 0.5 mm. The mounting holes are located at the corners, with a diameter of 4.9 mm and a radius of R2.5. The distance between the mounting holes is 68 mm.



KEY TECHNOLOGY(CHINA)LIMITED

深圳市键特电子有限公司



www.rugged-key.com www.rugged-key.cn

Part Name				Project Name				
Part No.	K-TEK-B68KP-AC-BL-DWP			Project No.				
Material				Scale	1:1	Unit	mm	
Date	2023.02.09	Version	1.0	Tolerance	IT12	Sheet	1 of 1	
Designed	Wei Baoquan	Audited	Tony Deng		Approved			