



Head Office: B702, Building 1, Tianan Cyber Park, No. 524, Qinglin Road, Huanggekeng Community, Longcheng Subdistrict, Long Gang District, Shenzhen, Guangdong, P.R.China

Factory ADD.: Floor 7, Building S8, Fenggang Tianan Cyber Park, No. 208 Fenggang Section, Dongshen Road, Fenggang Town, Dongguan, Guangdong, P.R.China

Tel: +86 755 89239859, 89230460 Fax: +86 755 89312576


Website: [www.rugged-system.com](http://www.rugged-system.com), [www.rugged-key.com](http://www.rugged-key.com)

E-mail: [sales01@rugged-system.com](mailto:sales01@rugged-system.com), [sales05@rugged-system.com](mailto:sales05@rugged-system.com)

**Model NO:** K-TEK-M64-OMS-DT

**DESCRIPTION:** IP68 dynamic sealed & Ruggedized 5 keys Waterproof, Hygienic Optical Mouse with durable coating & antimicrobial mouse surface withstand to most chemicals and liquids under harsh environments, the mouse is full sized and features a 5-buttons designed for right & left clicking and scrolling up and down just like a conventional non-waterproof mouse, and it is a fully sealed IP68 and compatible with both USB and PS/2.

**DIMENSIONS :** 64.0mm x 126.0mm x 35.0mm (L x W x H)





® **Key Technology Rugged System Ltd**  
**东莞市键特电子有限公司**



Head Office: B702, Building 1, Tianan Cyber Park, No. 524, Qinglin Road, Huanggekeng Community, Longcheng Subdistrict, Long Gang District, Shenzhen, Guangdong, P.R.China

Factory ADD.: Floor 7, Building S8, Fenggang Tianan Cyber Park, No. 208 Fenggang Section, Dongshen Road, Fenggang Town, Dongguan, Guangdong, P.R.China

Tel: +86 755 89239859, 89230460 Fax: +86 755 89312576

Website: [www.rugged-system.com](http://www.rugged-system.com), [www.rugged-key.com](http://www.rugged-key.com)

E-mail: [sales01@rugged-system.com](mailto:sales01@rugged-system.com), [sales05@rugged-system.com](mailto:sales05@rugged-system.com)

<b>MECHANICAL DATA</b>	
Actuator/keys	5 keys
G.W.	0.3KG
Dimension	64.0mm x 126.0mm 35.0mm (L x W x H)
Color	White, black
<b>ELECTRICAL DATA</b>	
Supply Voltage	DC +5V±5%
Current Rating	30mA
EMC Standard	EN 55032:2015 EN 55035:2017
Lifespan	> 5 years
Switch Contact Material	Carbon-on-Gold key switch technology PCB
Interface	PS2, USB available
OS	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).
<b>ENVIRONMENTAL ADAPTABILITY</b>	
Operating temperature	-20°C to +65°C
Storage temperature	-30°C to +75°C
Operating RH	30-90%
Atmospheric pressure	60-106Kpa
Saline mist	96 hours, IEC 60512-6
Damp heat test at +40°C	21 days, IEC 60512-6
Dry heat test at +85°C	10 days, IEC 60512-6
<b>RELIABILITY</b>	
RoHS Compliant, CE and FCC, MIL-STD-461G (EMC, EMI, EMS, ESD) and MIL-STD-810H (high and low wide working temperature, low pressure, humidity, vibration, shock, salt spray, temperature shock, drop, rain, sand and dust, fungus, solar radiation etc.) optional.	
Protection Level	IP68
Key Lifespan	>5 million actuations
MTBF	>20000H
MTTR	<30min
APPLICATION	Industrial, coal and mine, medical and pharmaceutical, military and navy etc.

