


## MODEL NO: RGD-TPC-AR0800T-0004

## **Product Features:**

- 1 Rexchip RK3588 Processor
- 2 8-inch LED display
- 3 Android mobile operating system
- One rectangular plug, including one power supply
  One Gigabit network
  One serial port, one power supply (5w) serial port
  One power supply (5w)





## **TECHNICAL SPECIFICATIONS:**

Processor: Rexchip RK3588 Processor

Memory: DDR4 8GB

Harddisk: SSD 128 GB

Touch Screen: Capacitive touch screen, support multi-touch

Display: 8 inches LED display, 1920\*1200 resolution

OS: Android mobile operating system

Battery: Li-ion battery 6000mAh

Audio: Built-in speaker

Positioning System: Support Beidou positioning

Ports: 1\*DC input (aviation plug) Power connector, 1\*serial port (aviation plug) Serial port,

8-12V output (Air Plug) Power Output, 1\*Gigabit network port (plug) Network Interface

Dimension: 220m\*140mm\* 16mm (excluding protrusions such as plugs, feet, etc.)

**Cabinet Color: Black** 

Material: Magnesium aluminium alloy

Weight: 0.65KG





## **TECHNICAL SPECIFICATIONS:**

MTBF: ≥3000h

MTTR: ≤ 30min

Working Temperature: -20°C ~ +50°C

Storage Temperature: -40°C~ +60°C

Humidity: 95%  $\pm$ 3%, 30 °C ~60 °C, 48h, no condensation (switch off)

Waterproof Level: IP67

Electromagnetic Compatibility:

MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, salt spray temperature show programmed the shock of the shock

solar radiation etc.)

Safety:

Structural safety: Shell without sharp edges and corners

Insulation safety: Insulation resistance between power input and housing >  $100M\Omega$ 

Dielectric strength: Apply AC 1500V test voltage between the input of power adapter and the casing, and no breakdown, flying arc and

flickering will occur during the test. No breakdown, flying arc and flickering during the test.

Leakage current: Leakage current between chassis and ground > 3.5mA

